

Application Specification

Dated: 02 April 2014

Scope of work: Using Holdfast MS Sealants with of Marshall Innovations SUPER-STICK to ascertain Compatibility and Application

Introduction:

Marshall Innovations SUPER-STICK Building Tape® is a high performance window and door flashing tape designed to be installed down to -5deg°C.

Holdfast (NZ) Ltd MS Sealant products that are covered by this application specification are:

- Fix All 220MS
- Fix All Firestop MS
- Fix All HG MS
- Soudaseal 240FC

Application and instructions:

1. There are no compatibility issues between Holdfast NZ Ltd MS Sealants and the SUPER-STICK supplied by Marshall Innovations.
2. Apply SUPER-STICK as per the Install Instructions from Marshall Innovations
3. Clean the area of the foil backing to the SUPER-STICK area to be sealed by wiping the surface using the Gorilla Solvent Cleaner (Code#37013) or 696 Surface Activator (Code#19391) applied to a clean lint free cloth.
4. Wait a period of not less than 15min between wiping the surface before applying the Holdfast MS Sealant.
5. If required apply a PEF Rod so that the depth of sealant remains constant.
6. Apply a appropriate bead of Holdfast MS Sealant (Please see above Holdfast MS Sealants List) in accordance with the appropriate MS Sealant(s) Technical Data Sheet along the area that has been cleaned with Gorilla Solvent Cleaner (Code#37013) or 696 Surface Activator (Code#19391) at the joint area
7. Use a finishing tool to correctly form the sealant to the required shape and depth
8. Allow to cure

For further technical data please refer to Holdfast product data sheets available on line at www.holdfast.co.nz

The information, and, in particular, the recommendations relating to the application and end-use of Holdfast products, are given in good faith based on Holdfast NZ Ltd's current knowledge and experience of the products when properly stored, handled and applied under normal conditions.

In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered.

Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request. If you are in any doubt about the use of this product, or further information is required, contact the Holdfast Technical Department (0800 TECSPEC).