

Pro-Seal 45 ^{PLUS}

SPECIFICATION

PRODUCT DESCRIPTION

Pro-Seal45 Plus is a UV stable self-adhering general-purpose sealing tape. The tape has a white aluminium facer with an aggressive adhesive which forms a strong bond to most substrates.

Used as a general-purpose UV stable tape for repairs around the home.

- Not a substitute for flexible window flashing tapes.

WARRANTY

Please refer to

<https://www.mwnz.com/file/flashing-tapes-product-warranty/open>

For warranty documentation.

FEATURES & BENEFITS

- Aggressive adhesive that bonds to most substrates
- UV resistant
- No primers required
- Fast & easy installation

SURFACE PREPERATION

Surfaces must be clean, dry and free of any foreign materials, large gaps sharp edges and protrusions.

Always test substrate for compatibility prior to full application of tape.

APPLICATION

Cut the tape to the required length and width. Remove 100mm of the release film and press into place, continue removing the release film whilst applying pressure as the tape is applied. After tape is installed, roll all new applied tape with a firm roller to enhance adhesion.

Ensure all laps are in a shingle fashion so water flows over the lap not against it.

Laps must be a minimum of 50mm.

LIMITATIONS

- Should not come into contact with solvent based products, PVC's, TPO's, EPDM & Bitumen roofing materials.
- Not suitable for permanent water immersion.